



August 12, 2025

[Click Here to Place a Order](#)

[Click Here to Inquire about In-Stock Finished Extrusions](#)

PLYMOUTH® IN-STOCK MATERIAL SOLUTIONS											
Facility	Grade	Spec	Process	Finish	OD	ID	Wall	Length	Pcs	Total Quantity	UM
Eupora	1010	A-519	WELDED	Spheroidize Anneal	0.938	0.78	0.079	20	24	480	FT
Eupora	1010	J-2467	WELDED	Soft Anneal	0.649	0.571	0.039	12	100	1200	FT
Eupora	1010	J525	SEAMLESS	Soft Anneal	0.475	0.4	0.0375	20	17	340	FT
Eupora	1010	J525	WELDED	Soft Anneal	0.279	0.135	0.072	14	52	728	FT
Eupora	1010	J525	WELDED	Soft Anneal	0.758	0	0.06	12	18	216	FT
Eupora	1010	J525	WELDED	Soft Anneal	0.758	0	0.06	12	42	504	FT
Eupora	1010	Mil-T 6736B	WELDED	Cond N	0.399	0.306	0.0465	13.75	113	1553.8	FT
Eupora	1010	--	WELDED	--	0.279	0.135	0.072	14	58	812	FT
Eupora	1010	--	WELDED	--	0.279	0.135	0.072	14	124	1736	FT
Eupora	1010H	A-513-5	WELDED	Stress Relieve Anneal	0.5	0.43	0.035	20	67	1340	FT
Eupora	1010H	A-513-5	WELDED	Stress Relieve Anneal	0.5	0.43	0.035	20	302	6040	FT
Eupora	1010H	A-513-5	WELDED	Stress Relieve Anneal	0.5	0.43	0.035	20	320	6400	FT
Eupora	1010H	A-513-5	WELDED	Stress Relieve Anneal	0.75	0.584	0.083	24	15	360	FT
Eupora	1010H	A-513-5	WELDED	Stress Relieve Anneal	0.75	0.584	0.083	24	21	504	FT
Eupora	1010H	A-513-5	WELDED	Stress Relieve Anneal	0.75	0.584	0.083	24	125	3000	FT
Eupora	1010H	A-513-5	WELDED	Stress Relieve Anneal	0.75	0.584	0.083	24	169	4056	FT
Eupora	1010H	A519	WELDED	Stress Relieve Anneal	0.5	0.43	0.035	20	25	500	FT
Eupora	1010H	J525	WELDED	Soft Anneal	0.25	0.134	0.058	12	34	408	FT
Eupora	1010H	J525	WELDED	Soft Anneal	0.25	0.152	0.049	20	9	180	FT
Eupora	1010H	J525	WELDED	Soft Anneal	0.325	0.257	0.028	12	429	5148	FT
Eupora	1010H	J525	WELDED	Soft Anneal	0.375	0.277	0.049	20	34	680	FT
Eupora	1010H	--	WELDED	--	0.375	0.277	0.049	20	37	740	FT
Eupora	1010H	--	WELDED	--	0.375	0.277	0.049	20.5	41	840.5	FT
Eupora	1010H	--	WELDED	--	0.5	0.334	0.083	12	286	3432	FT
Eupora	1010H	--	WELDED	--	0.5	0.37	0.065	16	53	848	FT
Eupora	1010H	--	WELDED	--	0.5	0.37	0.065	20	63	1260	FT
Eupora	1010H	--	WELDED	--	0.5	0.37	0.065	20	197	3940	FT
Eupora	1010H	--	WELDED	--	0.5	0.418	0.041	20	119	2380	FT
Eupora	1010H	--	WELDED	--	0.625	0.459	0.083	20	11	220	FT
Eupora	1010H	--	WELDED	--	0.625	0.459	0.083	20	31	620	FT
Eupora	1010H	--	WELDED	--	0.625	0.459	0.083	20	41	820	FT
Eupora	1010H	--	WELDED	--	0.625	0.435	0.095	21	19	399	FT
Eupora	1010H	--	WELDED	--	0.75	0.584	0.083	20	25	500	FT
Eupora	1010H	--	WELDED	--	0.75	0.62	0.065	20	23	460	FT
Eupora	1010H	--	WELDED	--	0.75	0.51	0.12	20	7	140	FT
Eupora	1010H	--	WELDED	--	1	0.76	0.12	12	42	504	FT
Eupora	1010H	--	WELDED	--	1.25	1.01	0.12	20	17	340	FT
Eupora	1010H	--	WELDED	--	1.25	1.01	0.12	20	91	1820	FT
Eupora	1010H	--	WELDED	--	1.25	1.032	0.109	12	55	660	FT
Eupora	1010H	--	WELDED	--	1.25	1.06	0.095	15	36	540	FT
Eupora	1010H	--	WELDED	--	1.25	1.06	0.095	20	20	400	FT
Eupora	1010H	--	WELDED	--	1.25	1.12	0.065	20	6	120	FT
Eupora	1010H	--	WELDED	--	1.25	1.12	0.065	20	9	180	FT
Eupora	1010H	--	WELDED	--	1.5	1.35	0.075	23	10	230	FT
Eupora	1010H	--	WELDED	--	1.5	1.37	0.065	20	39	780	FT
Eupora	1018	A-513-5	SEAMLESS	Stress Relieve Anneal	0.868	0.732	0.053	12.667	125	1583.4	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	0.5	0.334	0.083	24	64	1536	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	0.625	0.375	0.125	23	65	1495	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	0.688	0.522	0.083	24	25	600	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	0.688	0.557	0.0655	12	17	204	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1	0.884	0.058	12	83	996	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1.375	1.135	0.12	19.5	15	292.5	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1.375	1.305	0.035	23.75	9	213.8	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1.375	1.305	0.035	23.75	36	855	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1.5	1.26	0.12	22.917	38	870.8	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1.5	1.402	0.049	23.833	30	715	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1.5	1.25	0.125	20	29	580	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1.75	1.51	0.12	24	16	384	FT
Eupora	1020	A-513-5	WELDED	Stress Relieve Anneal	1.586	1.396	0.095	20	48	960	FT
Eupora	1020	A-513-5	WELDED	Unannealed	1.75	1.51	0.12	11.333	90	1020	FT
Eupora	1020	A-513-5	WELDED	Unannealed	1.5625	1.3445	0.109	20	3	60	FT
Eupora	1020	A519	WELDED	Splined OD	1.5	1.282	0.109	21	52	1092	FT



August 12, 2025

[Click Here to Place a Order](#)

[Click Here to Inquire about In-Stock Finished Extrusions](#)

PLYMOUTH® IN-STOCK MATERIAL SOLUTIONS											
Facility	Grade	Spec	Process	Finish	OD	ID	Wall	Length	Pcs	Total Quantity	UM
Eupora	1020	A-519	WELDED	Spheroidize Anneal	0.625	0.375	0.125	19	217	4123	FT
Eupora	1020	A-519	WELDED	Spheroidize Anneal	0.625	0.375	0.125	23	60	1380	FT
Eupora	1020	A-519	WELDED	Spheroidize Anneal	1	0.884	0.058	12	93	1116	FT
Eupora	1020	A-519	WELDED	Spheroidize Anneal	1	0.93	0.035	11.667	86	1003.4	FT
Eupora	1020	J-2467	WELDED	Soft Anneal	0.625	0.375	0.125	19	135	2565	FT
Eupora	1020	J-2467	WELDED	Soft Anneal	0.625	0.375	0.125	19	217	4123	FT
Eupora	1020	J-2467	WELDED	Soft Anneal	0.625	0.385	0.12	21	131	2751	FT
Eupora	1020	J-2467	WELDED	Soft Anneal	0.625	0.472	0.0765	12	79	948	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.438	0.272	0.083	21.98	41	901.2	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.438	0.272	0.083	22	27	594	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.438	0.272	0.083	23	104	2392	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.5	0.282	0.109	24	33	792	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.5	0.384	0.058	12	61	732	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.5	0.384	0.058	12	91	1092	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.625	0.375	0.125	23	21	483	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.625	0.385	0.12	21	91	1911	FT
Eupora	1020	J525	WELDED	Soft Anneal	0.688	0.498	0.095	24	12	288	FT
Eupora	1020	J525	WELDED	Soft Anneal	1.25	1.01	0.12	20	18	360	FT
Eupora	1020	Mil-T 6736B	WELDED	Cond N	0.313	0.215	0.049	24	91	2184	FT
Eupora	1020	Mil-T 6736B	WELDED	Cond N	0.313	0.193	0.06	12	191	2292	FT
Eupora	1020	Mil-T 6736B	WELDED	Cond N	0.375	0.245	0.065	22	90	1980	FT
Eupora	1020	Mil-T 6736B	WELDED	Cond N	0.375	0.277	0.049	22	36	792	FT
Eupora	1020	Mil-T 6736B	WELDED	Cond N	0.625	0.375	0.125	19	217	4123	FT
Eupora	1020	Mil-T 6736B	WELDED	Cond N	1.313	1.147	0.083	22	4	88	FT
Eupora	1020	SA-214	WELDED	Soft Anneal	0.5	0.26	0.12	24	20	480	FT
Eupora	1020	--	WELDED	--	0.25	0.152	0.049	24	32	768	FT
Eupora	1020	--	WELDED	--	0.75	0.625	0.0625	18.75	23	431.3	FT
Eupora	1020	--	WELDED	--	0.875	0.635	0.12	11.5	14	161	FT
Eupora	1020	--	WELDED	--	1	0.76	0.12	20	127	2540	FT
Eupora	1020	--	WELDED	--	1	0.76	0.12	24	89	2136	FT
Eupora	1020	--	WELDED	--	1	0.773	0.1135	17	63	1071	FT
Eupora	1020	--	WELDED	--	1	0.81	0.095	22.5	10	225	FT
Eupora	1020	--	WELDED	--	1	0.81	0.095	22.5	25	562.5	FT
Eupora	1020	--	WELDED	--	1	0.884	0.058	12	38	456	FT
Eupora	1020	--	WELDED	--	1	0.884	0.058	12	83	996	FT
Eupora	1020	--	WELDED	--	1.125	0.885	0.12	22.5	9	202.5	FT
Eupora	1020	--	WELDED	--	1.125	0.885	0.12	22.5	14	315	FT
Eupora	1020	--	WELDED	--	1.125	0.885	0.12	22.583	8	180.7	FT
Eupora	1021	A-513-5	TUBE	Stress Relieve Anneal	0.5	0.37	0.065	24	10	240	FT
Eupora	1021	A-513-5	TUBE	Stress Relieve Anneal	0.5	0.37	0.065	24	42	1008	FT
Eupora	1021	A-513-5	TUBE	Stress Relieve Anneal	0.625	0.459	0.083	20	45	900	FT
Eupora	1021	A-513-5	TUBE	Stress Relieve Anneal	1	0.81	0.095	24	30	720	FT
Eupora	1021	A-513-5	TUBE	Stress Relieve Anneal	1	0.81	0.095	24	34	816	FT
Eupora	1021	A-513-5	TUBE	Unannealed	0.5	0.37	0.065	24	4	96	FT
Eupora	1021	J525	TUBE	Soft Anneal	0.75	0.56	0.095	24	26	624	FT
Eupora	1021	--	TUBE	--	1	0.76	0.12	24	7	168	FT
Eupora	1021	--	TUBE	--	1	0.76	0.12	24	27	648	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	0.3125	0.1825	0.065	23	17	391	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	0.3175	0.1825	0.0675	12	37	444	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	0.37	0.203	0.0835	35	62	1540	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	0.375	0.305	0.035	19.833	27	535.5	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	0.438	0.248	0.095	40	19	760	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	0.5	0.26	0.12	21	11	231	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	0.5	0.31	0.095	24	12	288	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	0.509	0.444	0.028	20	42	840	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1	0.76	0.12	19.67	11	216.4	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1	0.782	0.109	10	12	120	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1	0.782	0.109	10.167	8	81.3	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1	0.782	0.109	12	28	336	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1	0.87	0.065	20.5	21	430.5	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1	0.87	0.065	21.5	48	1032	FT



August 12, 2025

[Click Here to Place a Order](#)

[Click Here to Inquire about In-Stock Finished Extrusions](#)

PLYMOUTH® IN-STOCK MATERIAL SOLUTIONS											
Facility	Grade	Spec	Process	Finish	OD	ID	Wall	Length	Pcs	Total Quantity	UM
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1	0.87	0.065	22.833	12	274	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1.125	1.055	0.035	24	20	480	FT
Eupora	4130	A-513-5	SEAMLESS	Stress Relieve Anneal	1.5	1.188	0.156	20	5	100	FT
Eupora	4130	A-513-5	SEAMLESS	Unannealed	1.25	1.01	0.12	23.583	18	424.5	FT
Eupora	4130	A-513-5	SEAMLESS	Unannealed	1.75	1.584	0.083	18.5	6	111	FT
Eupora	4130	J525	SEAMLESS	Soft Anneal	0.75	0.56	0.095	10	70	700	FT
Eupora	4130	J525	SEAMLESS	Soft Anneal	1.25	0.982	0.134	10	22	220	FT
Eupora	4130	Mil-T 6736B	SEAMLESS	Cond N	1	0.884	0.058	22	7	154	FT
Eupora	4130	Mil-T 6736B	SEAMLESS	Cond N	1	0.884	0.058	22	11	242	FT
Salisbury	304	--	WELDED	--	0.1875	0.1475	0.02	980	--	37	LB
Salisbury	304 L	--	SEAMLESS	--	0.5	0.26	0.12	1547	--	898	LB
Salisbury	304 L	--	SEAMLESS	--	0.633	0.517	0.058	350	--	118	LB
Salisbury	304 L	--	SEAMLESS	--	0.75	0.51	0.12	14	--	10.7221	LB
Salisbury	304 L	--	SEAMLESS	--	0.75	0.51	0.12	24	--	18.3807	LB
Salisbury	304 L	--	SEAMLESS	--	0.75	0.51	0.12	171	--	130.9622	LB
Salisbury	304 L	--	SEAMLESS	--	0.75	0.51	0.12	168	--	128.6647	LB
Salisbury	304 L	--	SEAMLESS	--	0.75	0.51	0.12	220	--	168.4894	LB
Salisbury	304 L	--	SEAMLESS	--	0.75	0.51	0.12	65	--	49.781	LB
Salisbury	304/304L	--	SEAMLESS	--	0.5	0.43	0.035	12	--	2.593	LB
Salisbury	304/304L	--	SEAMLESS	--	0.5	0.43	0.035	8	--	1.7286	LB
Salisbury	304/304L	--	SEAMLESS	--	0.5	0.43	0.035	144	--	31.1156	LB
Salisbury	304/304L	--	SEAMLESS	--	0.5	0.43	0.035	80	--	17.2864	LB
Salisbury	304/304L	--	SEAMLESS	--	0.5	0.43	0.035	68	--	14.6935	LB
Salisbury	304/304L	--	SEAMLESS	--	0.5	0.43	0.035	285	--	61.5829	LB
Salisbury	304/304L	--	SEAMLESS	--	0.625	0.555	0.035	195	--	40	LB
Salisbury	304/304L	--	SEAMLESS	--	0.702	0.546	0.078	130	--	79	LB
Salisbury	304/304L	--	SEAMLESS	--	0.73	0.629	0.0505	735	--	267	LB
Salisbury	304/304L	--	SEAMLESS	--	0.73	0.629	0.0505	672	--	241	LB
Salisbury	304/304L	--	SEAMLESS	--	0.73	0.629	0.0505	840	--	293	LB
Salisbury	304/304L	--	SEAMLESS	--	1	0.902	0.049	24	--	13.299	LB
Salisbury	304/304L	--	SEAMLESS	--	1	0.902	0.049	70	--	38.7887	LB
Salisbury	304/304L	--	SEAMLESS	--	1	0.902	0.049	120	--	66.4948	LB
Salisbury	304/304L	--	SEAMLESS	--	1	0.902	0.049	144	--	79.7938	LB
Salisbury	304/304L	--	SEAMLESS	--	1	0.902	0.049	30	--	16.6237	LB
Salisbury	304/304L	--	SEAMLESS	--	1	0.93	0.035	378	--	231	LB
Salisbury	304H	--	SEAMLESS	--	0.25	0.21	0.02	480	--	27	LB
Salisbury	304H	--	SEAMLESS	--	0.25	0.21	0.02	2412	--	120.6	LB
Salisbury	304H	--	SEAMLESS	--	0.375	0.277	0.049	585	--	111	LB
Salisbury	304H	--	SEAMLESS	--	0.375	0.305	0.035	363	--	56.2324	LB
Salisbury	304H	--	SEAMLESS	--	0.375	0.305	0.035	360	--	55.7676	LB
Salisbury	304H	--	SEAMLESS	--	0.5	0.43	0.035	325	--	55	LB
Salisbury	304H	--	SEAMLESS	--	0.5	0.444	0.028	40	--	5.6872	LB
Salisbury	304H	--	SEAMLESS	--	0.5	0.444	0.028	98	--	13.9336	LB
Salisbury	304H	--	SEAMLESS	--	0.5	0.444	0.028	32	--	4.5498	LB
Salisbury	304H	--	SEAMLESS	--	0.5	0.444	0.028	76	--	10.8057	LB
Salisbury	304H	--	SEAMLESS	--	0.5	0.444	0.028	465	--	47	LB
Salisbury	304H	--	SEAMLESS	--	0.5	0.444	0.028	176	--	25.0237	LB
Salisbury	304H	--	SEAMLESS	--	0.625	0.527	0.049	860	--	260	LB
Salisbury	304H	--	SEAMLESS	--	0.625	0.555	0.035	70	--	15.4545	LB
Salisbury	304H	--	SEAMLESS	--	0.625	0.555	0.035	108	--	23.8442	LB
Salisbury	304H	--	SEAMLESS	--	0.625	0.555	0.035	45	--	9.9351	LB
Salisbury	304H	--	SEAMLESS	--	0.625	0.555	0.035	1200	--	298	LB
Salisbury	304H	--	SEAMLESS	--	0.625	0.555	0.035	52	--	11.4805	LB
Salisbury	304H	--	SEAMLESS	--	0.625	0.555	0.035	110	--	24.2857	LB
Salisbury	304H	--	SEAMLESS	--	0.753	0.647	0.053	280	--	147	LB
Salisbury	304H	--	SEAMLESS	--	1	0.87	0.065	588	--	389	LB
Salisbury	304H	--	SEAMLESS	--	1	0.902	0.049	24	--	11.4495	LB
Salisbury	304H	--	SEAMLESS	--	1	0.902	0.049	171	--	81.578	LB
Salisbury	304H	--	SEAMLESS	--	1	0.902	0.049	42	--	20.0367	LB
Salisbury	304H	--	SEAMLESS	--	1	0.902	0.049	30	--	14.3119	LB
Salisbury	304H	--	SEAMLESS	--	1	0.902	0.049	60	--	28.6239	LB



August 12, 2025

[Click Here to Place a Order](#)

[Click Here to Inquire about In-Stock Finished Extrusions](#)

PLYMOUTH® IN-STOCK MATERIAL SOLUTIONS												
Facility	Grade	Spec	Process	Finish	OD	ID	Wall	Length	Pcs	Total Quantity	UM	
Salisbury	304L	--	WELDED	--	0.5	0.422	0.039	10	--	2.1233	LB	
Salisbury	304L	--	WELDED	--	0.5	0.422	0.039	24	--	5.0959	LB	
Salisbury	304L	--	WELDED	--	0.5	0.422	0.039	258	--	49	LB	
Salisbury	304L	--	WELDED	--	0.5	0.422	0.039	140	--	24	LB	
Salisbury	304L	--	WELDED	--	0.5	0.422	0.039	78	--	16.5616	LB	
Salisbury	304L	--	WELDED	--	0.5	0.422	0.039	700	--	120	LB	
Salisbury	304L	--	WELDED	--	0.5	0.422	0.039	5	--	1.0616	LB	
Salisbury	304L	--	WELDED	--	0.5	0.422	0.039	175	--	37.1575	LB	
Salisbury	304L	--	WELDED	--	0.5	0.46	0.02	531	--	76	LB	
Salisbury	304L	--	WELDED	--	0.5	0.46	0.02	216	--	22	LB	
Salisbury	304L	--	WELDED	--	0.5	0.46	0.02	880	--	79	LB	
Salisbury	304L	--	WELDED	--	0.6505	0.5645	0.043	798	--	272	LB	
Salisbury	304L	--	WELDED	--	0.6505	0.5645	0.043	4075	--	1057	LB	
Salisbury	304L	--	WELDED	--	0.6505	0.5645	0.043	252	--	103	LB	
Salisbury	304L	--	WELDED	--	0.6505	0.5645	0.043	1440	--	405	LB	
Salisbury	304L	--	WELDED	--	0.6505	0.5645	0.043	1170	--	398	LB	
Salisbury	304L	--	WELDED	--	0.6505	0.5645	0.043	342	--	102	LB	
Salisbury	304L	--	WELDED	--	0.6505	0.5645	0.043	546	--	174	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	15	--	2.5942	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	32	--	5.5344	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	140	--	25.3217	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	28	--	4.8426	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	36	--	6.2262	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	30	--	5.4261	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	1088	--	207.9822	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	780	--	154	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	560	--	161	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	494	--	82	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	2950.5	--	564.0178	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	176	--	31.833	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	72	--	11.2688	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	345	--	53.9964	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	432	--	67.6129	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	340	--	58.8027	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	720	--	130.2261	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	621	--	97.1935	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	920	--	143.9904	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	121	--	18.9379	LB	
Salisbury	304L	--	WELDED	--	0.7025	0.6495	0.0265	84	--	15.193	LB	
Salisbury	304L	--	WELDED	--	0.315	0.237	0.039	264	--	38	LB	
Salisbury	304L	--	WELDED	--	0.605	0.519	0.043	8850.16	--	2469	LB	
Salisbury	316/316L	--	SEAMLESS	--	0.317	0.1564	0.0803	620	--	125	LB	
Salisbury	316L	--	SEAMLESS	--	0.25	0.194	0.028	792	--	66	LB	
Salisbury	316L	--	SEAMLESS	--	0.3125	0.1809	0.0658	3300	--	577	LB	
Salisbury	316L	--	SEAMLESS	--	0.313	0.21	0.0515	800	--	370	LB	
Salisbury	316L	--	SEAMLESS	--	0.317	0.117	0.1	1500	--	390	LB	
Salisbury	316L	--	SEAMLESS	--	0.317	0.117	0.1	660	--	157	LB	
Salisbury	316L	--	SEAMLESS	--	0.317	0.1564	0.0803	1000	--	330	LB	
Salisbury	316L	--	SEAMLESS	--	0.5	0.392	0.054	156	--	40	LB	
Salisbury	316L	--	SEAMLESS	--	0.5	0.392	0.054	702	--	180	LB	
Salisbury	316L	--	SEAMLESS	--	0.616	0.362	0.127	630	--	461	LB	
Salisbury	316L	--	SEAMLESS	--	0.6315	0.3919	0.1198	170	--	171	LB	
Salisbury	316L	--	SEAMLESS	--	0.6315	0.3919	0.1198	350	--	228	LB	
Salisbury	316L	--	SEAMLESS	--	0.683	0.503	0.09	108	--	79	LB	
Salisbury	316L	--	SEAMLESS	--	0.75	0.532	0.109	588	--	439	LB	
Salisbury	316L	--	SEAMLESS	--	0.75	0.532	0.109	1740	--	1599	LB	
Salisbury	316L	--	SEAMLESS	--	1	0.87	0.065	2112	--	1474	LB	
Salisbury	316L	--	SEAMLESS	--	0.59	0.472	0.059	155	--	53	LB	
Salisbury	316L	--	SEAMLESS	--	0.84	0.646	0.097	325	--	232	LB	
Salisbury	321	--	SEAMLESS	--	0.375	0.305	0.035	1776	--	233	LB	
Salisbury	321	--	SEAMLESS	--	0.375	0.305	0.035	888	--	117	LB	



August 12, 2025

[Click Here to Place a Order](#)

[Click Here to Inquire about In-Stock Finished Extrusions](#)

PLYMOUTH® IN-STOCK MATERIAL SOLUTIONS											
Facility	Grade	Spec	Process	Finish	OD	ID	Wall	Length	Pcs	Total Quantity	UM
Salisbury	321	--	SEAMLESS	--	0.375	0.319	0.028	200	--	19	LB
Salisbury	321	--	SEAMLESS	--	0.375	0.319	0.028	410	--	35	LB
Salisbury	321	--	SEAMLESS	--	0.5	0.402	0.049	252	--	78	LB
Salisbury	321	--	SEAMLESS	--	0.5	0.402	0.049	414	--	146	LB
Salisbury	321	--	SEAMLESS	--	0.5	0.402	0.049	558	--	186	LB
Salisbury	321	--	SEAMLESS	--	0.5	0.402	0.049	279	--	149	LB
Salisbury	321	--	SEAMLESS	--	0.5	0.46	0.02	143	--	14.6106	LB
Salisbury	321	--	SEAMLESS	--	0.5	0.46	0.02	600	--	61.3033	LB
Salisbury	321	--	SEAMLESS	--	0.5	0.46	0.02	500	--	51.0861	LB
Salisbury	321	--	SEAMLESS	--	0.625	0.555	0.035	420	--	107	LB
Salisbury	321	--	SEAMLESS	--	0.625	0.555	0.035	120	--	32	LB
Salisbury	321	--	SEAMLESS	--	0.625	0.555	0.035	414	--	65	LB
Salisbury	321	--	SEAMLESS	--	0.625	0.555	0.035	330	--	64	LB
Salisbury	321	--	SEAMLESS	--	0.625	0.569	0.028	195	--	37	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	11	--	7.3333	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	26	--	17.3333	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	27.8	--	19.1377	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	32	--	21.3333	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	820	--	621	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	1480	--	994	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	36	--	24.7826	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	8.5	--	5.8514	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	320	--	222	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	10.5	--	7	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	10.5	--	7.2283	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.56	0.095	75	--	50	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.62	0.065	280	--	196	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.62	0.065	135	--	65	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.652	0.049	17	--	5.8502	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.652	0.049	20	--	6.8826	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.652	0.049	40	--	13.7652	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.652	0.049	70	--	24.0891	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.652	0.049	52	--	17.8947	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.652	0.049	323	--	69	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.652	0.049	48	--	16.5182	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.654	0.048	204	--	79	LB
Salisbury	321	--	SEAMLESS	--	0.75	0.694	0.028	575	--	74	LB
Salisbury	321	--	SEAMLESS	--	0.785	0.687	0.049	450	--	179	LB
Salisbury	321	--	SEAMLESS	--	1	0.76	0.12	78	--	131	LB
Salisbury	321	--	SEAMLESS	--	1	0.834	0.083	128	--	139	LB
Salisbury	321	--	SEAMLESS	--	1	0.834	0.083	376	--	518	LB
Salisbury	321	--	SEAMLESS	--	1	0.834	0.083	330	--	280	LB
Salisbury	321	--	SEAMLESS	--	1	0.902	0.049	156	--	75	LB
Salisbury	321	--	SEAMLESS	--	1	0.93	0.035	143	--	58	LB
Salisbury	321	--	SEAMLESS	--	1	0.944	0.028	1512	--	447	LB
Salisbury	321	--	SEAMLESS	--	1	0.944	0.028	345	--	93	LB
Salisbury	321	--	WELDED	--	0.187	0.117	0.035	645	--	38	LB
Salisbury	347	--	SEAMLESS	--	0.375	0.319	0.028	960	--	100	LB
Salisbury	347	--	SEAMLESS	--	0.75	0.694	0.028	264	--	71.0769	LB
Salisbury	347	--	SEAMLESS	--	0.75	0.694	0.028	640	--	143	LB
Salisbury	347	--	SEAMLESS	--	0.75	0.694	0.028	30	--	8.0769	LB
Salisbury	347	--	SEAMLESS	--	0.75	0.694	0.028	44	--	11.8462	LB
Salisbury	600	--	SEAMLESS	--	0.372	0.268	0.052	336	--	90	LB
Salisbury	600	--	SEAMLESS	--	0.491	0.445	0.023	3300	--	429	LB
Salisbury	600	--	SEAMLESS	--	0.491	0.445	0.023	3120	--	385	LB
Salisbury	600	--	SEAMLESS	--	0.491	0.445	0.023	2948	--	370	LB
Salisbury	600	--	SEAMLESS	--	0.493	0.447	0.023	1936	--	210	LB
Salisbury	600	--	SEAMLESS	--	0.493	0.447	0.023	3267	--	405	LB
Salisbury	600	--	SEAMLESS	--	0.906	0.802	0.052	160	--	81	LB
Salisbury	600	--	SEAMLESS	--	1.151	1.025	0.063	260	--	288	LB
Salisbury	600	--	SEAMLESS	--	1.152	1.016	0.068	270	--	244	LB



August 12, 2025

[Click Here to Place a Order](#)

[Click Here to Inquire about In-Stock Finished Extrusions](#)

PLYMOUTH® IN-STOCK MATERIAL SOLUTIONS											
Facility	Grade	Spec	Process	Finish	OD	ID	Wall	Length	Pcs	Total Quantity	UM
Salisbury	600	--	SEAMLESS	--	1.178	1.032	0.073	24	--	22	LB
Salisbury	600	--	SEAMLESS	--	1.376	1.162	0.107	70	--	88	LB
Salisbury	625	--	SEAMLESS	--	0.25	0.194	0.028	987	--	75	LB
Salisbury	625	--	SEAMLESS	--	0.312	0.256	0.028	58	--	66	LB
Salisbury	625	--	SEAMLESS	--	0.375	0.277	0.049	870	--	149	LB
Salisbury	625	--	SEAMLESS	--	0.375	0.277	0.049	1530	--	201	LB
Salisbury	625	--	SEAMLESS	--	0.5	0.402	0.049	9	--	5.5419	LB
Salisbury	625	--	SEAMLESS	--	0.5	0.402	0.049	28	--	17.2414	LB
Salisbury	625	--	SEAMLESS	--	0.5	0.402	0.049	160	--	98.5222	LB
Salisbury	625	--	SEAMLESS	--	0.5	0.402	0.049	6	--	3.6946	LB
Salisbury	625	--	SEAMLESS	--	0.5	0.444	0.028	790	--	132	LB
Salisbury	625	--	SEAMLESS	--	0.5	0.444	0.028	290	--	49	LB
Salisbury	625	--	SEAMLESS	--	0.75	0.62	0.065	437	--	137	LB
Salisbury	625	--	SEAMLESS	--	0.875	0.819	0.028	451	--	141	LB
Salisbury	625	--	SEAMLESS	--	1	0.834	0.083	290	--	348	LB
Trent	17-7 PH	--	WELDED	--	0.75	0.62	0.065	121.91	22	57.7	LB
Trent	17-7 PH	--	WELDED	--	0.75	0.62	0.065	23.99	22	11.36	LB
Trent	17-7 PH	--	WELDED	--	0.75	0.62	0.065	1606.5	208	760.51	LB
Trent	17-7 PH	--	WELDED	--	0.75	0.62	0.065	3081.25	380	1458.51	LB
Trent	17-7 PH	--	WELDED	--	0.89	0.704	0.093	270	15	212.76	LB
Trent	17-7 PH	--	WELDED	--	0.89	0.704	0.093	2052	228	1616.96	LB
Trent	17-7 PH	--	WELDED	--	1.259	1.077	0.091	141.3	21	159.67	LB
Trent	17-7 PH	--	WELDED	--	1.259	1.077	0.091	1056.45	157	1193.75	LB
Trent	17-7 PH	--	WELDED	--	1.385	1.2	0.0925	297.5	35	378.12	LB
Trent	17-7 PH	--	WELDED	--	0.79	0.66	0.065	410.5	0	205.66	LB
Trent	17-7 PH	--	WELDED	--	0.79	0.66	0.065	1417.33	0	710.08	LB
Trent	21-6-9	--	WELDED	--	0.1875	0.1475	0.02	606	89	21.65	LB
Trent	21-6-9	--	WELDED	--	0.1875	0.1315	0.028	4715.16	253	221.61	LB
Trent	21-6-9	--	WELDED	--	0.25	0.18	0.035	1183.24	50	95.01	LB
Trent	21-6-9	--	WELDED	--	0.25	0.21	0.02	554.66	84	27.22	LB
Trent	21-6-9	--	WELDED	--	0.25	0.21	0.02	1098.91	0	53.93	LB
Trent	21-6-9	--	WELDED	--	0.25	0.21	0.02	163.91	7	8.04	LB
Trent	21-6-9	--	WELDED	--	0.25	0.21	0.02	48	4	2.35	LB
Trent	21-6-9	--	WELDED	--	0.3125	0.2565	0.028	398.33	58	31.86	LB
Trent	21-6-9	--	WELDED	--	0.375	0.305	0.035	169.5	23	21.51	LB
Trent	21-6-9	--	WELDED	--	0.375	0.305	0.035	79.41	11	10.08	LB
Trent	21-6-9	--	WELDED	--	0.375	0.305	0.035	640.83	89	81.38	LB
Trent	21-6-9	--	WELDED	--	0.375	0.319	0.028	11	14	1.1	LB
Trent	21-6-9	--	WELDED	--	0.375	0.319	0.028	145.49	14	14.55	LB
Trent	21-6-9	--	WELDED	--	0.375	0.319	0.028	717.83	69	71.78	LB
Trent	21-6-9	--	WELDED	--	0.375	0.319	0.028	187.08	20	18.7	LB
Trent	21-6-9	--	WELDED	--	0.375	0.323	0.026	299.33	24	29.03	LB
Trent	21-6-9	--	WELDED	--	0.375	0.335	0.02	217.99	32	30.76	LB
Trent	21-6-9	--	WELDED	--	0.375	0.335	0.02	380	33	28.5	LB
Trent	21-6-9	--	WELDED	--	0.375	0.335	0.02	264	22	19.98	LB
Trent	21-6-9	--	WELDED	--	0.375	0.335	0.02	108.99	15	8.25	LB
Trent	21-6-9	--	WELDED	--	0.375	0.335	0.02	94.16	14	7.12	LB
Trent	21-6-9	--	WELDED	--	0.375	0.335	0.02	54.33	9	4.11	LB
Trent	21-6-9	--	WELDED	--	0.375	0.335	0.02	1729.74	94	130.94	LB
Trent	21-6-9	--	WELDED	--	0.375	0.343	0.016	312	13	19.12	LB
Trent	21-6-9	--	WELDED	--	0.5	0.37	0.065	297.66	13	89.89	LB
Trent	21-6-9	--	WELDED	--	0.5	0.448	0.026	159	20	20.67	LB
Trent	21-6-9	--	WELDED	--	0.5	0.448	0.026	154.66	23	20.1	LB
Trent	21-6-9	--	WELDED	--	0.5	0.448	0.026	812.33	90	106.8	LB
Trent	21-6-9	--	WELDED	--	0.5	0.448	0.026	768.74	108	100.7	LB
Trent	21-6-9	--	WELDED	--	0.5	0.448	0.026	335.66	39	43.97	LB
Trent	21-6-9	--	WELDED	--	0.625	0.517	0.054	808	101	258.56	LB
Trent	21-6-9	--	WELDED	--	0.75	0.62	0.065	401.16	41	190.56	LB
Trent	21-6-9	--	WELDED	--	0.75	0.62	0.065	191.08	25	90.76	LB
Trent	21-6-9	--	WELDED	--	0.75	0.62	0.065	5250.91	250	2494.18	LB
Trent	21-6-9	--	WELDED	--	0.75	0.672	0.039	1043	91	308.55	LB



August 12, 2025

[Click Here to Place a Order](#)

[Click Here to Inquire about In-Stock Finished Extrusions](#)

PLYMOUTH® IN-STOCK MATERIAL SOLUTIONS												
Facility	Grade	Spec	Process	Finish	OD	ID	Wall	Length	Pcs	Total Quantity	UM	
Trent	21-6-9	--	WELDED	--	0.75	0.68	0.035	569.33	50	148.02	LB	
Trent	21-6-9	--	WELDED	--	0.75	0.68	0.035	1329.16	79	345.58	LB	
Trent	21-6-9	--	WELDED	--	1	0.896	0.052	446.58	29	234.87	LB	
Trent	21-6-9	--	WELDED	--	1	0.896	0.052	3051.83	161	1605.05	LB	
Trent	21-6-9	--	WELDED	--	1.25	1.12	0.065	360.33	0	296.11	LB	
Trent	21-6-9	--	WELDED	--	1.25	1.152	0.049	1315.58	114	815.66	LB	
Trent	21-6-9	--	WELDED	--	1.25	1.152	0.049	1130.25	100	700.75	LB	
Trent	21-6-9	--	WELDED	--	1.25	1.152	0.049	214.25	31	134.51	LB	
Trent	21-6-9	--	WELDED	--	1.25	1.152	0.049	547.33	83	343.64	LB	
Trent	21-6-9	--	WELDED	--	1.25	1.194	0.028	314.75	42	114.89	LB	
Trent	21-6-9	--	WELDED	--	1.25	1.18	0.035	305.83	42	138.54	LB	
Trent	21-6-9	--	WELDED	--	3.25	3.07	0.09	156	13	473.33	LB	
Trent	304	--	WELDED	--	3.252	3.122	0.065	11.33	1	25.27	LB	
Trent	304	--	WELDED	--	3.252	3.122	0.065	82.5	1	183.97	LB	
Trent	304	--	WELDED	--	3.502	3.372	0.065	124.16	11	298	LB	
Trent	304	--	WELDED	--	3.502	3.372	0.065	14.83	11	35.59	LB	
Trent	304	--	WELDED	--	3.541	3.411	0.065	58.16	4	139.59	LB	
Trent	304/304L	--	WELDED	--	2	1.87	0.065	66	3	89.1	LB	
Trent	304/304L	--	WELDED	--	3.5	3.38	0.06	72.83	15	161.69	LB	
Trent	304/304L	--	WELDED	--	3.5	3.38	0.06	59.83	15	132.82	LB	
Trent	304L	--	WELDED	--	1.388	0.973	0.2075	2520.5	207	6654.12	LB	
Trent	304L	--	WELDED	--	1.5	1.37	0.065	261.83	11	263.32	LB	
Trent	304L	--	WELDED	--	1.744	1.494	0.125	664.5	29	1448.61	LB	
Trent	304L	--	WELDED	--	1.999	1.813	0.093	105.75	9	202.1	LB	
Trent	304L	--	WELDED	--	3.5	3.38	0.06	193	30	428.46	LB	
Trent	316	--	WELDED	--	3.234	3.06	0.087	318.58	28	940.45	LB	
Trent	321	--	WELDED	--	1.5	1.46	0.02	388.66	29	123.98	LB	
Trent	321	--	WELDED	--	1.75	1.68	0.035	170	25	110.02	LB	
Trent	321	--	WELDED	--	1.75	1.694	0.028	86.41	12	44.92	LB	
Trent	625	--	WELDED	--	1.5	1.444	0.028	790.08	71	374.43	LB	
Trent	625	--	WELDED	--	1.5	1.444	0.028	143.83	14	67.6	LB	
Trent	625	--	WELDED	--	1.5	1.444	0.028	10.33	71	4.89	LB	
Trent	625	--	WELDED	--	2.145	2.045	0.05	128.41	7	154.1	LB	
Trent	625	--	WELDED	--	2.5	2.34	0.08	60.75	11	134.86	LB	
Trent	625	--	WELDED	--	3	2.84	0.08	51.91	7	139.13	LB	
Trent	718	--	WELDED	--	1.125	1.069	0.028	129.75	9	44.47	LB	
Trent	718	--	WELDED	--	1.25	1.194	0.028	310.25	27	117.89	LB	
Trent	718	--	WELDED	--	1.5	1.37	0.065	646.91	31	672.79	LB	
Trent	718	--	WELDED	--	1.5	1.402	0.049	425	0	335.75	LB	
Trent	718	--	WELDED	--	2.25	2.194	0.028	222.41	30	154.41	LB	
Trent	AL6XN	--	WELDED	--	1	0.78	0.11	960	20	1031.04	LB	
Trent	304/304L	--	WELDED	--	3.5	3.38	0.06	59.83	15	132.82	LB	
Trent	304L	--	WELDED	--	1.388	0.973	0.2075	2520.5	207	6654.12	LB	
Trent	304L	--	WELDED	--	1.5	1.37	0.065	261.83	11	263.32	LB	
Trent	304L	--	WELDED	--	1.744	1.494	0.125	664.5	29	1448.61	LB	
Trent	304L	--	WELDED	--	1.999	1.813	0.093	105.75	9	202.1	LB	
Trent	304L	--	WELDED	--	3.5	3.38	0.06	193	30	428.46	LB	
Trent	316	--	WELDED	--	3.234	3.06	0.087	318.58	28	940.45	LB	
Trent	321	--	WELDED	--	1.5	1.46	0.02	388.66	29	123.98	LB	
Trent	321	--	WELDED	--	1.75	1.68	0.035	170	25	110.02	LB	
Trent	321	--	WELDED	--	1.75	1.694	0.028	86.41	12	44.92	LB	
Trent	625	--	WELDED	--	1.5	1.444	0.028	790.08	71	374.43	LB	
Trent	625	--	WELDED	--	1.5	1.444	0.028	143.83	14	67.6	LB	
Trent	625	--	WELDED	--	1.5	1.444	0.028	10.33	71	4.89	LB	
Trent	625	--	WELDED	--	2.145	2.045	0.05	128.41	7	154.1	LB	
Trent	625	--	WELDED	--	2.5	2.34	0.08	60.75	11	134.86	LB	
Trent	718	--	WELDED	--	1.125	1.069	0.028	129.75	9	44.47	LB	
Trent	718	--	WELDED	--	1.25	1.194	0.028	310.25	27	117.89	LB	
Trent	718	--	WELDED	--	1.5	1.37	0.065	646.91	31	672.79	LB	
Trent	718	--	WELDED	--	1.5	1.402	0.049	425	0	335.75	LB	



In-Stock Material Solutions

August 12, 2025

[Click Here to Place a Order](#)

[Click Here to Inquire about In-Stock Finished Extrusions](#)

PLYMOUTH® IN-STOCK MATERIAL SOLUTIONS											
Facility	Grade	Spec	Process	Finish	OD	ID	Wall	Length	Pcs	Total Quantity	UM
Trent	718	--	WELDED	--	2.25	2.194	0.028	222.41	30	154.41	LB
Trent	AL6XN	--	WELDED	--	1	0.78	0.11	960	20	1031.04	LB